

DOOR POSITION SENSOR DPS 6100





A MORTISED MECHANICAL HIGH SECURITY DOOR POSITION SWITCH

- The Airteq 6100 series DPS offers maximum security for use in access-sensitive areas for swinging doors
 where a built-in mechanical door indication switch is desired.
- Available for doors up to 48" wide
- Flush mounted into a prepared frame and door
- Self Adjusting switch.
- Provided with security torx fasteners

STANDARD FEATURES

- 180° maximum door swing
- Simple, tool-free adjustment
- Supplied with 3 Pin connector with color coded pigtail
- Corrosion resistant

OPTIONAL FEATURES

- Field side pigtail for connection to locks by other manufacturers
- Double Circuit: Provides an additional SPDT switch to be triggered by the DPS, Specify –2

TECHNICAL DATA


- Handed: Specify LH Door or RH Door application
- Concealed (in Frame): 1" H x 1 1/2" W x 7 1/2" L
- Control Arm: 5/16" thick Steel, zinc plated
- Door Mounted Track:.75" H x 1.53" W x 9.375" L
- Face Plate: 11ga (1/8") Stainless Steel
- Switch Rated for 5A at 30VDC & 250 VAC (SPDT)


Warranty

Airteq warrants its products against defects in material or workmanship for one year from the time of delivery. Airteq's sole obligation under the warranty is to repair, or at its option, to replace the product. The buyer shall have no other remedy. (All special, incidental and coincidental damages are excluded.) Written notice of breach of warranty must be given to Airteq within the warranty period. The warranty does not cover damages resulting from improper installation or maintenance, accident or misuse. NO OTH-ER WARRANTIES AS TO MERCHANTABILITY OR OTHERWISE ARE MADE. A continuing product research program is ongoing. Airteq reserves the right to incorporate products and specification changes at any time without notice.



2511 Midpark Rd., Montgomery, AL 36109 Phone: (800) 466-3007 Fax: (334) 286-6421





I	2	I	1		
	REVISIONS				
	DESCRIPTION		DATE	APPROVED	
					D
-					

С

(PART NUMBER		Length	DESCRIPTION				В
	340-0000-125			SWI	TCH, MICRO S	SWITCH #3	11SM1	
	340-0000-202				MALE .062 DI #350628-1 or M		• • • • • • • • • • • • • • • • • • • •	
	340-1800-007		6.25"	Black W	IRE, 18AWG, 7	' STRD, UL	1015/1007	
	340-1800-008		6"	White W	IRE, 18AWG, 7	' STRD, UL	1015/1007	
	340-1800-009 6		6.5"	Red WI	RE, 18AWG, 7	STRD, UL1	015/1007	
DATE NAME								
3/9/17 MER		•					-	
6100 DPS SWITCH ASSEMBLY								A
SIZE DWG. NO. REV								
			SCA	ALE: 3:2	WEIGHT:	SHE	et 1 of 1	
2				I		1		